



- NOTES:
- CURRENT RATING: 7A/PIN FOR POWER PIN(PIN1,PIN7).
 - DURABILITY: 10000C CYCLES.
 - MATING FORCE INITIAL: 25N MAX.
AFTER DURABILITY: 25N MAX.
UNMATING FORCE INITIAL: 8~25N.
AFTER DURABILITY: 5~25N.
 - ALL DIMENSIONS MARKER (**) MUST BE MEASURE BY FAI.
 - ALL DIMENSIONS MARKER ▼ MUST BE CONTROLLED BY QC.
 - GP PASSED ACCORD WITH HRD-RoHS-219 STANDARD.

TOP SHELL	STAINLESS STEEL (SUS304-H, T=0.30mm)	50~120u" NI UNDER PLATED OVERALL
BOTTOM SHELL	STAINLESS STEEL (SUS304-H, T=0.30mm)	50~150u" TIN UNDER PLATED OVERALL
SUPPORT PLATE	STAINLESS STEEL (SUS304-3/4H, T=0.10mm)	CLEAN
CONTACT	COPPER ALLOY (C7025-TM03, T=0.20mm)	50u" Ni MIN UNDER PLATING OVERALL A区 30u" Au MIN ON CONTACT AREA B区 1u" Au MIN ON CONTACT AREA 1u" Au MIN ON SOLDER AREA
I/M	HPPA-TH830, 全新料 BLACK, UL 94V-0	/
PART	MATERIAL	FINISH

PIN ASSIGNMENTS	
PIN1	VBUS
PIN2	VBUS
PIN3	D-
PIN4	D+
PIN5	ID
PIN6	GND
PIN7	GND

REV.	ECN NO.	DESCRIPTION	DATE	mm	DATE:	X. ±0.25	X.* ±3.00'	CHECKED:	PART NO.
B		更新弹片高度尺寸	2019.06.07		2018.10.26	.X ±0.20	.X' ±2.00'		U71-0B07D110
A		NEW	2018.10.26		SCALE:	.XX ±0.15	.X' ±2.00'	APPROVE:	NAME:
					1:1	.XXX ±0.10	.XX' ±1.0		MICRO USB 7PIN 板上1.14mm
					SHEET:				DRAWING NO.
					1/1				C-U71-0000
					REV. A				
					FINISH				
					SEE NOTE				

DATE/CODE:
HXXXXXX

I=HRD

线别(A=A线、B=B线...)
班别(1=白班, 2=夜班...)
日期(5=5日, A=10日...)
月份(5=5月, A=10月...)

VD 昆山捷皇电子精密科技有限公司
HONGRIDA ELECTRONIC TECHNOLOGY CO.,LTD.

