


NOTES:

- MATERIAL:**  
 BODY: HI-TEMP. PLASTIC, BLACK, UL 94V-0  
 TERMINAL: COPPER ALLOY, T=0.10mm  
 SHELL: STAINLESS STEEL T=0.10mm
- FINISH:**  
 TERMINAL: 50u" Ni MIN UNDER PLATING OVER ALL  
 GOLD FLASH ON CONTACT AREA  
 TIN 60-200u" PLATED ON SOLDER TAIL AREA  
 SHELL: 50u" Ni MIN UNDER PLATING OVER ALL  
 AU 1~3u" PLATED ON SOLDER TAIL AREA
- ALL DIMENSIONS MARKED ▼ MUST BE CONTROLLED BY QC.
- GP PASSED ACCORD WITH HRD-RoHS-219 STANDARD
- ALL DIMENSIONS MARKER (XX) MUST BE MEASURED BY FAI.

				UNITS: mm	GENERAL TOLERANCE		DRAW:	PART NO: B57-AB04F15C
				DATE: 12/04/2015	X. ±0.25	X." ±2.00'	CHECKED:	TITLE: 1.50H 侧压式 4PIN BATTERY 2.50PITCH
B0			08/20/2016	SCALE: 10:1	.X ±0.10	.XX' ±0.50'	APPROVE:	DRAWING NO:
A		NEW	12/04/2015	SHEET: 1/1	.XXX ±0.05	.XXX' ±0.10'		
REV.	ECN NO.	DESCRIPTION	DATE	REV. A	FINISH: SEE NOTE		 <b>昆山捷皇电子精密科技有限公司</b> HONGRIDA ELECTRONIC TECHNOLOGY CO., LTD.	