



- NOTES:
- MATERIAL:
 BODY: HI-TEMP. PLASTIC, BLACK, UL 94V-0
 TERMINAL: COPPER ALLOY, T=0.20mm
 SHELL: STAINLESS STEEL T=0.10mm
 - FINISH:
 TERMINA:
 50 μ Ni MIN UNDER PLATING OVER ALL
 GOLD FLASH 1~3 μ ON CONTACT AREA
 60-200 μ TIN PLATED ON SOLDER TAIL AREA
 SHELL:
 50 μ Ni MIN UNDER PLATING OVER ALL
 GOLD FLASH 1~3 μ ON SOLDER TAIL AREA
 - ALL DIMENSIONS MARKED ▼ MUST BE CONTROLLED BY QC
 - GP PASSED ACCORD WITH RoHS STANDARD
 - ALL DIMENSIONS MARKER (XX) MUST BE MEASURE BY FAI.

RECOMMENDED PCB LAYOUT (TOLERANCE ± 0.05)

				UNITS: mm	GENERAL TOLERANCE		DRAW:	PART NO:
				DATE: 08/22/2015	X. ± 0.20	X." $\pm 2.00'$	CHECKED:	TITLE:
				SCALE: 8 / 1	.X ± 0.15	.X' $\pm 1.00'$	APPROVE:	BAATTERY 沉板1.30
B	E1511433A	改善铁壳松动	11/18/2015	SHEET: 8 / 1	.XX ± 0.10	.XX' $\pm 0.50'$		DRAWING NO:
A	E1508291A	料号变更	08/22/2015	SHEET: 1 / 1	MATERIAL:			
REV.	ECN NO.	DESCRIPTION	DATE	REV. B	FINISH: SEE NOTE			

