



- NOTES:
- MATERIAL:
HOUSING: NYLON-9T, BLACK, UL 94 HB
TERMINAL: MIC/GND/R AUDIO C5210, T=0.20mm
L AUDIO/DETECT SUS304, T=0.20mm
 - FINISH:
TERMINA: 50u" MIN Ni PLATED OVER ALL,
15u" MIN AU PLATED ON CONTACT AREA
1u" MIN AU PLATED ON SOLDER AREA
 - ALL DIMENSIONS MARKED ▼ MUST BE CONTROLLED BY QC
 - ALL DIMENSIONS MARKED (XX) MUST BE MEASURE BY FAI
 - PRODUCT SPECIFICATIONS:
5-1 WITHSTANDING: 500VAC/MINUTE
5-2 CONTACT RESISTANCE: 50 MILLIOHM (initial) Max.
5-3 MATING AND UNMATING FORCE : 1.0-2.0 Kgf Max. (BTFORE DURABILITY)
5-4 MATING AND UNMATING FORCE : 0.5-2.0 Kgf Max. (AFTER DURABILITY)
5-5 OPERATION TEMPERATURE : -25° TO +85°
5-6 STORAGE TEMPERATURE : -25° TO +85°
5-7 DURABILITY : 5000 CYCLES

NAME	MATERIAL	FINISH	QTY
HOUSING	NYLON-9T, BLACK, UL 94 HB		1
Mylar	KAPTON T=0.06mm	/	1
DETECT	SUS304 T=0.20mm	50U" MIN Ni UNDER PLATED OVER ALL 15U" MIN AU ON CONTACT AREA 1U" MIN AU ON SOLDER AREA	1
L AUDIO			1
R AUDIO			1
GND	C5210 T=0.20mm		1
MIC			1

REV.	ECN NO.	DESCRIPTION	DATE	REV.	FINISH: SEE NOTE	DRAW:	PART NO:
A		NEW	06/21/2017	1/1		CHECKED:	PH95-0B18C43M
						APPROVE:	TITLE: Ø3.50MM PHONE JACK CONN. 板上1.80mm * 总高4.30mm
							DRAWING NO:



昆山捷皇电子精密科技有限公司
HONGRIDA ELECTRONIC TECHNOLOGY CO., LTD.